

DT313SC-MD/ DT313T-MD Medical Tablets

Slim, Anti-microbial, UL60601-1 Certified Tablet for Efficient Operations



The DT313SC-MD/ DT313T-MD Medical Tablet features the integration of a brilliant 13.3" capacitive touch screen and a high performance, energy-efficient Intel® Celeron® or Core™ i5/ i7 series processor within a slim, lightweight, durable package. With built-in Wi-Fi and Bluetooth as well as options for cameras and barcode scanner, this robust tablet offers health professionals an effective tool to monitor, record and retrieve patient information. With its large, vivid display, the DT313SC-MD/ DT313T-MD Medical Tablet shows a wide work area and detailed application interface to enhance user experience and workflow.

Features



- 13.3" full-HD LCD display with capacitive touch, digital pen support
- Intel® Celeron®, 8th Generation Core™ i5/i7 processor
- Microsoft® Windows® 10 IoT Enterprise operating system
- UL60601-1 certified with anti-microbial enclosure
- High capacity, hot-swappable battery pack
- Built-in foldable tabletop stand and optional handle
- Optional 4K (3840 x 2160) LCD
- Optional cameras, 2D barcode scanner



Applications

- Hospital
- Medical Office
- Health Field Services
- Emergency Services
- Patient Surveys
- Public Safety

Specifications

		
Model	DT313SC-MD	DT313T-MD
System		
CPU	Intel® Celeron® dual-core processor	Intel® 8 th Generation Core™ i5 or i7 quad-core processor
RAM	4GB	8GB to 16GB
Storage	128GB to 256GB Flash	128GB to 2TB Flash
Operating System	Microsoft® Windows® 10 IoT Enterprise	Microsoft® Windows® 10 IoT Enterprise
Display	13.3" LED-backlight screen with capacitive touch, digital pen support	13.3" LED-backlight screen with capacitive touch, digital pen support
Display Resolution	1920 x 1080 3840 x 2160 (optional)	1920 x 1080 3840 x 2160 (optional)
Control Switch and Buttons	1 power button, 1 trigger button, 3 programmable buttons	
Speaker	Built-in speaker	Built-in speaker
Network Interface		
WLAN	Wi-Fi 802.11ac, 2.4GHz/ 5GHz dual band	
Bluetooth	Bluetooth 4.2 LE	Bluetooth 4.2 LE
I/O Ports		
USB Ports	USB 3.0 x 1, USB 2.0 x 2	USB 3.0 x 1, USB 2.0 x 2
Headset Jack	1 (3.5mm)	1 (3.5mm)
Ethernet Port	Ethernet 10/ 100/ 1000MB Base-T LAN	Ethernet 10/ 100/ 1000MB Base-T LAN
HDMI-out	1	1
DC-in	1	1
Mechanical and Environmental		
AC/DC Adapter	Input: 100 – 240V AC; Output: 19V DC, 3.42A	
Battery Pack	Hot swappable battery, 11.4V, 5400mAh Hot swappable battery, 11.4V, 8000mAh (optional)	
Enclosure	ABS + PC plastics and magnesium-aluminum alloy; anti-microbial enclosure	
Dimensions (H x W x D)	10.6 x 13.2 x 0.8 in/ 270 x 335 x 21 mm	10.6 x 13.2 x 0.8 in/ 270 x 335 x 21 mm
Weight	3.97 lbs/ 1.8 kg	3.97 lbs/ 1.8 kg
Regulatory	FCC Class B, UL60601-1, CE, RoHS compliant	
Temperature	Operation: -20°C – 40°C; Storage: -55°C – 70°C	
Humidity	0% – 90% non-condensing	
Major Options		
Barcode Scanner	2D scanner, reads 1D also	2D scanner, reads 1D also
Camera	2 megapixel front camera, and 8 megapixel back camera with auto focus, white balance, gain control and exposure control	

* Specifications subject to change without notice.

Accessories

